

SPECIAL PACKAGING INSTRUCTION

Form Approved - CC *7B*
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503. Please do not return your form to either of these addresses.

1. PART OR DRAWING NO. (GAGE) NOMENCLATURE 12387408 (19207) CABLE ASSEMBLY, SPEC		2. CODE IDENT 19207		3. SPT NO. AK14511098	
4. NATIONAL STOCK NO. 6150-01-451-1098		5. DATE OF DRAWING 11-30-98		6. REVISION	
7. QUP 1 EA	8. ICQ NONE	9. UNIT PACK WT. (LB) 1.7	10. UNIT PACK CU (CU. FT.) 0.136		11. UNIT PACK SIZE (INCHES) 8.3 X 8.3 X 3.4
12. MILITARY PRESERVATION MIL-P-116, METHOD IC-3		18. STEPS 1B	19. RECD 1	20. DESCRIPTION CUSHIONING: PPP-C-1797, TYPE I, SIZE: 22 X 11 X 1/4.	
13. CLEANING MIL-P-116, PROCESS C-1		2		BAG: MIL-B-117, TYPE I, CLASS B, STYLE 2, SIZE: 12 X 12.	
14. DRYING MIL-P-116		3C		CONTAINER: ASTM-D5118, TYPE CF, CLASS W/P, VARIETY SW, GRADE W6C, STYLE OPF SIZE: 8 X 8 X 3.	
15. PACKING MIL-STD-2073 AND NOTE D		16. MARKING MIL-STD-129		17. NOTES / DRAWING	

- A. COIL WIRING HARNESS, WITH CONNECTORS FACING INWARD, TO SPECIFIED DIMENSIONS, 7-1/2 X 7-1/2 X 2-1/2, AND SECURE SUFFICIENTLY TO PREVENT UNCOILING OF THE ITEM.
- B. SECURE WITH TAPE.
- C. CLOSE CONTAINER IN ACCORDANCE WITH ASTM-D1974; METHOD 2B3 OR 2B4.
- D. LEVEL A: PACKING SHALL BE ACCOMPLISHED USING A CLEATED PLYWOOD BOX, OVERSEAS TYPE, CONFORMING TO PPP-B-601 OR NAILED WOOD BOX CONFORMING TO CLASS 2 OF PPP-B-621.
 LEVEL B: THE UNIT CONTAINER IS AN ACCEPTABLE LEVEL B SHIPPING CONTAINER WHEN SEALED AND REINFORCED IN ACCORDANCE WITH ASTM-D1974; METHOD 2C OR 2D. FOR BOTH LEVEL A AND LEVEL B, WHEN THE TOTAL QUANTITY TO BE SHIPPED TO THE SAME DESTINATION EXCEEDS 125 POUNDS, EXTERIOR PACKS WITHOUT SKIDS SHALL BE PALLETIZED IN ACCORDANCE WITH MIL-STD-147.
- E. INSPECT THE PRESERVATION AND THE UNIT PACK IN ACCORDANCE WITH MIL-STD-2073-1. INSPECT THE PACKING IN ACCORDANCE WITH MIL-STD-1186 AND THE APPLICABLE CONTAINER SPECIFICATION.