

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

-MB

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS**

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE 12350003-1 (19207) PUMP, COOLING SYSTEM			2. CODE IDENT 19207		3. SPI NO. AK13200530	
4. NATIONAL STOCK NUMBER 2930-01-320-0530			5. DATE OF DRAWING 07-19-2011		6. REVISION B	
7. QUP 1 EA	8. ICQ NONE	9. UNIT PACK WT. (LB) 76.0	10. UNIT PACK CU (CU FT) 0.860		11. UNIT PACK SIZE (INCHES) 14.1 X 10.8 X 9.7	
12. MILITARY PRESERVATION (METHOD) MIL-STD-2073-1D, METHOD 42		18. STEPS 1-B	19. REQ'D	20. DESCRIPTION PRESERVATIVE: MIL-PRF-2104H, GR 15W-40		
13. CLEANING MIL-STD-2073-1D		2-C		CAPS/PLUGS: NAS 847		
		3-D		PRESERVATIVE: MIL-PRF-16173, GR 4		
14. DRYING MIL-STD-2073-1D		4-E		WRAP: MIL-PRF-121, TY II, SIZE: 43 X 26		
		5-F		BLOCKING/BRACING: ASTM-D6199, SEE NOTES		
		6-G		CONTAINER: ASTM-D5118, ST RSC, TY CF, CL D		
15. PACKING				V SW, GR 275, SIZE: 12-3/8 X 9-7/8 X 8-1/2		
a. LEVEL A MIL-STD-2073-1D AND NOTE J		7-H		BAG: MIL-DTL-117, TY I, CL E, ST 1, SIZE: 21 X 25		
		8-I		CONTAINER: ASTM-D5118, ST RSC, TY CF, CL WR		
b. LEVEL B MIL-STD-2073-1D AND NOTE J				V SW, GR V3c, SIZE: 10-3/8 X 9-3/8 X 13		
16. MARKING MIL-STD-129						

17. NOTES / DRAWING
- A. INSPECT PRESERVATION, UNIT PACK, AND PACKING IN ACCORDANCE WITH MIL-STD-2073-1D AND THE APPLICABLE CONTAINER SPECIFICATION
 - B. FLUSH INTERNALLY, ROTATE TO ASSURE COMPLETE COVERAGE AND DRAIN. IF INTERNAL PRESERVATION IS ACCOMPLISHED DURING MANUFACTURE AND IF MEASURES HAVE BEEN TAKEN TO PREVENT CONTAMINATION, INTERNAL PRESERVATION SHALL NOT BE REPEATED.
 - C. SEAL ALL FITTINGS AND OPENINGS WITH CAPS/PLUGS OF APPROPRIATE SIZE.
 - D. APPLY PRESERVATIVE TO ALL UNPAINTED, UNPLATED EXTERNAL METALLIC SURFACE.
 - E. WRAP ITEM ENTIRELY, SECURE WITH TAPE ASTM-D6123.
 - F. FOR BLOCKING/BRACING SIZE AND ORIENTATION, SEE PAGE 2.
 - G. CONTAINER CLOSURE SHALL BE IN ACCORDEANCE WITH ASTM D1974, METHOD 2B6.
 - H. CLOSE BAG BY HEAT SEAL.
 - I. CONTAINER CLOSURE SHALL BE IN ACCORDEANCE WITH ASTM D1974, METHOD 2B6.

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

-MB

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS**

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE 12350003-1 (19207) PUMP, COOLING SYSTEM	2. CODE IDENT 19207	3. SPI NO. AK13200530
4. NATIONAL STOCK NUMBER 2930-01-320-0530	5. DATE OF DRAWING 07-19-2011	6. REVISION B

17. NOTES / DRAWING

J. PACKING

LEVEL A PACKING SHALL BE ACCOMPLISHED USING WOOD-CLEATED PANELBOARD SHIPPING BOXES, CONFORMING TO ASTM-D 6251, TYPE III, CLASS 2 OR NAILED WOOD BOXES CONFORMING TO ASTM-D 6880, CLASS 2.

LEVEL B PACKING SHALL BE ACCOMPLISHED USING FIBERBOARD BOXES, WEATHER RESISTANT, CONFORMING TO ASTM-D 5118 OR TRIPLEWALL, CORRUGATED FIBERBOARD BOXES, CLASS 2, CONFORMING TO ASTM-D 5168. CLOSURE, SEALING, AND REINFORCEMENT SHALL BE IAW SPECIFIC, APPLICABLE METHODS OF ASTM-D 1974, OR AS REFERENCED IN THE CONTAINER SPECIFICATION.

WHEN THE TOTAL QUANTITY TO BE SHIPPED TO THE SAME DESTINATION EXCEEDS 125 POUNDS, EXTERIOR PACKS WITHOUT SKIDS SHALL BE PALLETIZED IN ACCORDANCE WITH MIL-STD-147.

