

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

XCL

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS**

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE SR4M (K7265) BOAT, UTILITY			2. CODE IDENT 19207		3. SPI NO. AK90751779	
4. NATIONAL STOCK NUMBER 1940-99-075-1779			5. DATE OF DRAWING 09-06-2011		6. REVISION -	
7. QUP 001	8. ICQ NONE	9. UNIT PACK WT. (LB) 505.0	10. UNIT PACK CU (CU FT) 112.642		11. UNIT PACK SIZE (INCHES) 143.0 X 57.0 X 26.0	
12. MILITARY PRESERVATION (METHOD) MIL-STD-2073-1D, METHOD 10			18. STEPS 1-B	19. REQ'D 1	20. DESCRIPTION VENDOR'S WEATHER RESISTANT FIBERBOARD BOX	
13. CLEANING MIL-STD-2073-1D						
14. DRYING MIL-STD-2073-1D						
15. PACKING						
a. LEVEL A MIL-STD-2073-1D AND NOTE C						
b. LEVEL B MIL-STD-2073-1D AND NOTE C						
16. MARKING MIL-STD-129						

17. NOTES / DRAWING

- A. THE PRESERVATION AND UNIT PACK IN ACCORDANCE WITH MIL-STD-2073-1. INSPECT THE PACKING IN ACCORDANCE WITH MIL-STD-1186 AND THE APPLICABLE CONTAINER SPECIFICATION.
- B. PRESERVE, PREPARE AND CONFIGURE THE ITEM FOR SHIPMENT AND STORAGE (UP TO TWO YEARS), BEFORE PLACING THE ITEM INTO THE CONTAINER.
- C. PACKING:

LEVEL A PACKING SHALL BE ACCOMPLISHED USING WOOD-CLEATED PANELBOARD SHIPPING BOXES, CONFORMING TO ASTM-D 6251, TYPE III, CLASS 2 OR NAILED WOOD BOXES CONFORMING TO ASTM-D 6880, CLASS 2.

LEVEL B PACKING SHALL BE ACCOMPLISHED USING FIBERBOARD BOXES, WEATHER RESISTANT, CONFORMING TO ASTM-D 5118 OR TRIPLEWALL, CORRUGATED FIBERBOARD BOXES, CLASS 2, CONFORMING TO ASTM-D 5168. CLOSURE, SEALING, AND REINFORCEMENT SHALL BE IAW SPECIFIC, APPLICABLE METHODS OF ASTM-D 1974, OR AS REFERENCED IN THE CONTAINER SPECIFICATION.

WHEN THE TOTAL QUANTITY TO BE SHIPPED TO THE SAME DESTINATION EXCEEDS 125 POUNDS, EXTERIOR PACKS WITHOUT SKIDS SHALL BE PALLETIZED IN ACCORDANCE WITH MIL-STD-147.