

SPECIAL PACKAGING INSTRUCTION

Form Approved XCJ
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS**

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE MIL-PRF-32349A TYPE II			2. CODE IDENT 19207		3. SPI NO.	
4. NATIONAL STOCK NUMBER			5. DATE OF DRAWING 10-04-11		6. REVISION A	
7. QUP 1 EA.	8. ICQ NONE	9. UNIT PACK WT. (LB) 2800	10. UNIT PACK CU (CU FT) 413.333		11. UNIT PACK SIZE (INCHES) 77.5 X 96.0 X 96.0	
12. MILITARY PRESERVATION (METHOD) MIL-STD-2073-1D, METHOD 10			18. STEPS	19. REQ'D	20. DESCRIPTION	
					SEE NOTES	
13. CLEANING MIL-STD-2073-1D						
14. DRYING MIL-STD-2073-1D						
15. PACKING						
a. LEVEL A MIL-STD-2073-1D AND NOTE B						
b. LEVEL B NOT APPLICABLE						
16. MARKING MIL-STD-129 AND NOTE C						

17. NOTES / DRAWING
- A. Quality Assurance Provisions: Inspect preservation and unit pack in accordance with MIL-STD-2073-1D. Inspect the packing in accordance with MIL-STD-1186 and the applicable container specification.
 - B. Packing is not required; the unit container shall also serve as the shipping container. Closure, sealing and reinforcement shall be in accordance with MIL-PRF-32349-A section 3.3.2.
 - C. Each Tricon shall be marked in accordance with MIL-PRF-32349A section 3.6. For an example, view figure 3 in MIL-PRF-32349A.
 - D. Any non-manufactured wood used inside the TRICON shall be heat-treated. All Wood Packaging Material shall be constructed from heat treated (treated to 56 degrees Celsius -core temperature- for 30 minutes) lumber and certified by an accredited agency accredited by the ALSC in accordance with Wood Packaging Material Policy and Wood Packaging Material Enforcement Regulations (see URL: <http://www.alsc.org>). The box/pallet manufacturer and the manufacturer of wood used as inner packaging shall ensure traceability to the original source of heat treatment. Marking: Each box/pallet shall be marked to show the conformance to the International Plant Protection Convention Standard. The quality mark shall be placed on both ends of the outer packaging, between the end cleats or end battens. Pallet markings shall be applied to the stringer or block on diagonally opposite sides and ends of the pallet and be contrasting and clearly visible. All dunnage used in configuring and/or securing the load shall also comply with ISPM15 and be marked with an ALSC approved dunnage stamp, marked at two foot intervals (in the case of dunnage shorter than 2 feet, each piece must still have the mark present). Foreign manufacturers shall have the heat treatment and marking of non-manufactured wood products verified in accordance with their National Plant Protection Organization's compliance program.