

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

XCR

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR COMPLETED FORM TO THE ABOVE ORGANIZATION.

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE DB2831-5209 (84760) FUEL INJECTION PUMP			2. CODE IDENT 19207		3. SPI NO. AK14679029	
4. NATIONAL STOCK NUMBER 2910-01-467-9029			5. DATE OF DRAWING 12-15-2011		6. REVISION	
7. QUP 1 EA.	8. ICQ NONE	9. UNIT PACK WT. (LB) 15.0 *	10. UNIT PACK CU (CU FT) 0.447 *		11. UNIT PACK SIZE (INCHES) 12.3 X 9.1 X 6.9 *	
12. MILITARY PRESERVATION (METHOD) MIL-STD-2073-1D, METHOD 42			18. STEPS 1-B	19. REQ'D	20. DESCRIPTION INTERNAL PRESERVATIVE: MIL-PRF-21260, GR.10	
			13. CLEANING MIL-STD-2073-1D	2-C		CLOSURE: NAS834
14. DRYING MIL-STD-2073-1D			4-E	1	MIL-PRF-121, TY. II, SIZE: SEE NOTE E	
			5-F		CUSHIONING: ASTM D4727, TY. CF, CL. DOM.	
15. PACKING			6-G	1	CONTAINER: ASTM D5118, TY. CF, CL. DOM, VAR. SW, GR. 275, ST. RSC, SIZE: SEE NOTE G	
			a. LEVEL A MIL-STD-2073-1D AND NOTE J	7-H	1	BAG: MIL-DTL-117, TY. II, CL. E, ST. 1, SIZE: SEE NOTE H
b. LEVEL B MIL-STD-2073-1D AND NOTE J			8-G	1	CONTAINER: ASTM D5118, TY. CF, CL. WR, GR. W5c, STYLE RSC, SIZE: SEE NOTE G	
			16. MARKING MIL-STD-129 AND NOTE I			

17. NOTES / DRAWING

* UNIT PACK WEIGHT, CUBE AND SIZE ARE ESTIMATED.

- A. PRESERVATION AND PACKING SHALL BE IN ACCORDANCE WITH MIL-STD-2073-1D.
- B. FLUSH OR SLUSH INTERNALLY AND THOROUGHLY DRAIN EXCESS.
- C. SEAL ALL OPENINGS WITH PLUGS OF THE APPROPRIATE SIZE.
- D. APPLY PRESERVATIVE TO ALL UNPAINTED/UNPLATED FERROUS SURFACES.
- E. CALCULATE SIZE OF WRAP IN ACCORDANCE WITH MIL-STD-2073, TABLE A-V. WRAP ITEM AND SECURE USING TAPE.
- F. CUSHION AND IMMOBILIZE ITEM USING VARIOUS VARIETIES AND OR GRADES OF ASTM D4727 CORRUGATED FIBERBOARD.
- G. CALCULATE SIZE OF CONTAINER IN ACCORDANCE WITH MIL-STD-2073, TABLE A-V. CLOSE CONTAINER IN ACCORDANCE WITH ASTM D 1974, METHOD 2B6.
- H. CALCULATE SIZE OF BAG IN ACCORDANCE WITH MIL-STD-2073, TABLE A-V. CLOSE BAG BY HEAT SEALING.
- I. THE UNIT CONTAINER SHALL ALSO BE MARKED ON THE TOP AND ONE SIDE, IN ACCORDANCE WITH MIL-STD-129-SPECIAL MARKINGS, "REUSABLE CONTAINER AND CUSHIONING, DO NOT DESTROY. OPEN ALONG TAPESEAMS, AS NEEDED, USING SHALLOW-BLADED KNIFE."

SPECIAL PACKAGING INSTRUCTIONForm Approved
OMB No. 0704-0188

XCR

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR COMPLETED FORM TO THE ABOVE ORGANIZATION.

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE DB2831-5209 (84760) FUEL INJECTION PUMP	2. CODE IDENT 19207	3. SPI NO. AK14679029
4. NATIONAL STOCK NUMBER 2910-01-467-9029	5. DATE OF DRAWING 12-15-2011	6. REVISION

17. NOTES / DRAWING

J. PACKING:

LEVEL A PACKING SHALL BE ACCOMPLISHED USING WOOD-CLEATED PANELBOARD SHIPPING BOXES, CONFORMING TO ASTM-D 6251, TYPE III, CLASS 2 OR NAILED WOOD BOXES CONFORMING TO ASTM-D 6880, CLASS 2.

LEVEL B PACKING SHALL BE ACCOMPLISHED USING FIBERBOARD BOXES, WEATHER RESISTANT, CONFORMING TO ASTM-D 5118 OR TRIPLEWALL, CORRUGATED FIBERBOARD BOXES, CLASS 2, CONFORMING TO ASTM-D 5168. CLOSURE, SEALING, AND REINFORCEMENT SHALL BE IAW SPECIFIC, APPLICABLE METHODS OF ASTM-D 1974, OR AS REFERENCED IN THE CONTAINER SPECIFICATION.

WHEN THE TOTAL QUANTITY TO BE SHIPPED TO THE SAME DESTINATION EXCEEDS 125 POUNDS, EXTERIOR PACKS WITHOUT SKIDS SHALL BE PALLETIZED IN ACCORDANCE WITH MIL-STD-147.